

XLT-C.A.T. 23 Lift

This lift is mounted on four heavy duty casters (2 continuous swivel and 2 locking swivel).

The XLT-C.A.T. 23 features dual, high strength leaf chain for lifting.

This machine features an all steel construction and a durable powder coated finish.

Keyed on/off switch prevents unauthorized operation of the unit.

Emergency down valve on base of unit.

Continuous top guard rail on cage for added safety.

Rolls through a commercial doorway.

Forklift pockets are standard.

Removable cage converts unit into a 350 lb. capacity material lift.

Adjustable outriggers, with non-marring pads, are self-storing and easy-to-use.

Priced and shipped complete and ready for immediate use.



Applications vary for this versatile lift . . .

Auditorium Maintenance, Lighting, Industrial and Commercial Settings to list a few.

With the optional Spanner Kit, applications increase to include maintenance over permanent structures and seating.

Spanner Kit



XLT-T15 "Spanner" Auditorium Kit allows a C.A.T. 23 Lift access above permanent seating.

Specifications - XLT-C.A.T. 23

Platform Height, maximum:	23' 7" (7.18 m)
Working Height, maximum:	30' (9.14 m)
Capacity:	300 lbs. (136 kg)
Machine Weight *:	820 lbs. (375 kg)
Base Width:	28" (.71 m)
Base Length:	61" (1.55 m)
Machine Height (stowed):	78½" (1.99 m)
Outrigger Pattern:	69" x 77" (1.75 m x 1.96 m)
Platform Dimensions:	26" x 26" (.66 m x .66 m)
Power Options:	DC 12V/92AH Deep Cycle Battery 15Amp. Charger Included
	AC 110V Pump
	Air Air Powered Unit, Motor Operates with Shop Air, 80 PSI - 150 CFM

* DC power option weight listed, deduct 66 lbs. (30 kg) for AC option.

Optional Equipment:

Part #	Description	Wt.
XLT-T3	Tool Box	5 lbs. (2.3 kg)
XLT-T4	Fluorescent Tube Holder	10 lbs. (4.5 kg)
XLT-T6	110V Outlet for Tools	3 lbs. (1.4 kg)
XLT-T7	19" x 26" Cage and Platform	35 lbs. (15.9 kg)
XLT-T9	Fiberglass Cage	65 lbs. (29.5 kg)
XLT-T14	Additional Height Package*	50 lbs. (22.7 kg)

* Available only as a factory installed option.

XLT-T15	Spanner Auditorium Kit	475 lbs. (216 kg)
Span Length Adjustment		7'10" - 9'8" (2.4 m-3 m)
Max. Span Height (to bottom of lift casters)		3'7" (1.1 m)
Width in Use (outriggers extended)		8'9" (2.7 m)
Dimensions		8'6"L x 2'11¼"W x 5'10¼"H